

SYRINGE PUMP



SP40

Features:

Applicable syringe size: 10, 20, 30, 50/60 ml.

Automatic syringe size detection.

Automatic anti-bolus.

Drug library.

Wireless management: central monitoring by Infusion Management System with maximum 255 Pumps.

Stackable up to 4 Syringe Pumps (4-in-1 Docking Station) or 6 Syringe Pumps (6-in-1 Docking Station) with single power cord.

www.resproindia.com

Specifications

RESPRO

Model	Sp40
Syringe Size	10, 20, 30, 50/60 ml
Applicable Syringe	Compatible with syringe of any standard
VTBI	0.1-9999 ml < 1000 ml in 0.1 ml increments ≥ 1000 ml in 1 ml increments
Flow Rate	Syringe 10 ml: 0.1-400 ml/h Syringe 20 ml: 0.1-600 ml/h Syringe 30 ml: 0.1-900 ml/h Syringe 50/60 ml: 0.1-1300 ml/h < 100 ml/h in 0.1 ml/h increments ≥ 100 ml/h in 1 ml/h increments
Bolus Rate	Syringe 10 ml: 400 ml/h Syringe 20 ml: 600 ml/h Syringe 30 ml: 900 ml/h Syringe 50/60 ml: 1300 ml/h
Anti-Bolus	Automatic
Accuracy	±2% (mechanical accuracy 1%)
Infusion Mode	Memory mode Flow rate: ml/min, ml/h Time-based Body weight: mg/kg/min, mg/kg/h, ug/kg/min, ug/kg/h etc.
KVO Rate	0.1-1 ml/h (in 0.1 ml/h increments)
Alarms	Occlusion, near empty, end program, low battery, end battery, AC power off, motor malfunction, system malfunction, reminder alarm, pressure sensor error, syringe installation error, syringe drop off
Additional Features	Real-time infused volume, automatic power switching, automatic syringe identification, mute key, purge, bolus, anti-bolus, system memory
Drug Library	Available
Occlusion Sensitivity	High, medium, low
Power Supply, AC	110/230 V (optional), 50/60 Hz, 20 VA
Battery	9.6±1.6 V, rechargeable
Battery Life	7 hours at 5 ml/h
Working Temperature	5-40°C
Relative Humidity	20-90%
Atmospheric Pressure	860-1060 hpa
Size	314*167*140 mm
Weight	2.5 kg
Safety Classification	Class II, type CF